

FreshWater OZONE PROGRAM

Maintenance Program for your spa.

EVERY TIME YOU USE YOUR SPA

- When you are finished using your spa...
- Put in 1 cap of Spa Shock in the filter area. If you have heavy usage you may need to add a teaspoon of chlorine.
- Run clean cycle (If your spa is not equipped with a clean cycle, run jets for 10 minutes). Close cover.

ONCE PER WEEK

- Check PH & Alkalinity with test strips (You should get no or a low chlorine reading because you are using such a small amount of chlorine).
- Adjust PH & Alkalinity as necessary with pH Increaser or pH Decreaser (**only add 1oz. at a time**). Run jets for 30 minutes, then retest in 2 to 3 hours. Continue to adjust 1oz. at a time if necessary, waiting to retest in 2 to 3 hours.
- Once PH & Alkalinity are in ideal range, put in 1 cap of Spa Shock and 1 teaspoon of chlorine (large spas may require a tablespoon).
- Run jets **with cover off** for 10 minutes.
- Do not leave colored spas uncovered when empty.
- Add Stain and Scale Control according to directions to prevent calcium buildup in plumbing and equipment.

ONCE PER MONTH

- Remove filters and wash them out with water hose nozzle and replace in the compartment. Some filter types can be placed in the dishwasher WITH NO SOAP on rinse cycle to clean.

ONCE EVERY 4 MONTHS (This is the manufacturers recommended time frame).

- Shut off power to spa. 110 volt models test trip the GFCI at the end of the cord and then unplug.
220 volt models ***Note:** On the following high performance models – Grandee, Vista, Envoy, Limelights and Caspian (All models vary by year – check your owner’s manual or start-up sheet from delivery). Shut down the 20 amp breaker first, then the 30 amp breaker. **On, all other, Hot Spring/Tiger River 220 volt models** shut down the 30 amp breaker first, then 20 amp breaker and remove filters. Spray on Filter Cleaner and Degreaser. Let cleaner penetrate for about an hour. Rinse thoroughly with water hose nozzle, and rotate filters to prolong filter life. Make sure filters are secure and power spa up.
110 volt plugged to outlet. 220 volt ****Note:** With the high performance models listed above–flip the 30 amp breaker on first to start water circulating (bubbles coming up from bottom of spa indicates circulation). Once water is circulating flip the 20 amp breaker on. **All other, Hot Spring/Tiger River 220 volt models** flip the 20 amp breaker on first to start water circulating. Once water is circulating, flip the 30 amp breaker on.
- Clean cover with mild soap and water. Then apply Cover Clean to save your cover from harmful UV rays and prolong covers life
- Clean spa exterior with mild soap and water. Then apply water based stain for wood exteriors or rinse well and wiped down if it is synthetic.
- Drain, clean, and refill spa *Remember to power down your spa, using the procedure mentioned above, before draining. Clean filters thoroughly. Always refill spa by placing your hose gently into the gray standpipe in your filter compartment where your AG+ silver ion cartridge goes. This insures that the equipment fills up first which helps prevent airlocks.
- Replace AG+ silver ion cartridge at this time. Remember to screw all filter caps in place.
- Add entire bottle of Spa Metal Gon or the recommended Start-up dose of Stain and Scale Control evenly around spa edge.
- ****Power up spa using procedure above.**

*****Filters need to be replaced within 1 to 2 years depending on usage of spa*****